



DN	15	20	25	32	40	50	80
L	62	75	88	100	108	125	185
H	55	62	62	77	82	96	140
W	95	120	140	160	180	250	
BSPT	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"

PERFORMANCE CRITERION LIST			
NOMINAL PRESSURE	4.0MPa		
TEST PRESSURE OF SHELL	6.0MPa		
TEST PRESSURE OF SEALINE	4.4MPa		
DISIGN PRESSURE	4.0MPa		
TOP WORK TEMPERATURE	150°C		
APPLY MEDIUM: WATER,STEAM,OIL			
DESIGN AND MANUFACTURE STANDARD			
DESIGN AND MANUFACTURE STANDARD: DIN3357			
INSPECTION AND TEST STANDARD: DIN3230			
THREADS DIMENSION: DIN2999			
12	BODY	ASTM A216 WCB	
11	SEALING RING	PTFE	
10	GASKET	PTFE	
9	STEM	ASTM A182 F6a	
8	PACKING	PTFE	
7	RING	ASTM A182 F304	
6	NUT	1025	
5	SPACER	UNS G15660	
4	HANDWHEEL	1Cr18Ni9Ti	
3	BALL	A182 F6a	
2	GASKET	PTFE	
1	BONNET	ASTM A216 WCB	
No.:	PARTS	MATERIAL	REMARKS

APPRD:  
RVWD:  
CHKD:  
DRWN:  
DSGD:  
DATE:

**HANSETEC**

2PQ11F40C DN15~80(1/2"~3")